

M A T E R I A L S A F E T Y D A T A S H E E T

EP 50 PART A

Page: 1

PRODUCT NAME: EP 50 PART A

MSDS NUMBER: EP 50-A

HMIS CODES: H F R P
3 2 1 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ADUREL INTERNATIONAL INC

**ADDRESS: 820 WATER ST
RACINE WI 53403**

EMERGENCY PHONE: 262-770-0845

INFORMATION PHONE: 800-860-5834

DATE: 1/1/05

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

WEIGHT REPORTABLE COMPONENTS PERCENT	CAS NUMBER	mm Hg	@ TEMP	VAPOR PRESSURE
ETHYLENE GLYCOL MONOPROPYL ETHER OSHA PEL: NA, ACGIH TLV: NA, OTHER: NA	2807-30-9	1.3	68	15
AROMATIC NAPHTHA	64742-95-6	10.3	68	10
TRIMETHYL BENZENE	95-63-6	2.8	77	5
XYLENE OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	1330-20-7	2.4	68	0

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***
N/A

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 279 deg F - 308 deg F SPECIFIC GRAVITY (H2O=1): 1.51
 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
 COATING V.O.C.: 3.93 lb/gal MATERIAL V.O.C.: 3.93 lb/gal
 SOLUBILITY IN WATER: NONE
 APPEARANCE AND ODOR: WHITE OPAQUE LIQUID/XYLENE ODOR

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 80 deg F METHOD USED: TCC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 15.8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES
 WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZELS ARE PREFERABLE.