

EP 50 PART B

Page: 1

PRODUCT NAME: EP 50 PART B
MSDS NUMBER: EP 50-B

HMS CODES: H F R P
3 2 1 G

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ADUREL INTERNATIONAL INC
ADDRESS: 820 WATER ST
RACINE WI 53403

EMERGENCY PHONE: 262-770-0845
INFORMATION PHONE: 800-860-5834 DATE: 1/1/05

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
AROMATIC NAPHTHA	64742-95-6	10.3 68	15
ETHYLENE GLYCOL MONOPROPYL ETHER OSHA PEL: NA, ACGIH TLV: NA, OTHER: NA	2807-30-9	1.3 68	10
TRIMETHYL BENZENE	95-63-6	2.8 77	5
XYLENE OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm	1330-20-7	2.4 68	0

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

N/A

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 279 deg F - 308 deg F SPECIFIC GRAVITY (H2O=1): 1.01
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 4.42 lb/gl MATERIAL V.O.C.: 4.42 lb/gl
SOLUBILITY IN WATER: NONE
APPEARANCE AND ODOR: WHITE OPAQUE LIQUID/XYLENE ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 80 deg F METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 15.8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZELS ARE PREFERABLE.